



Specifications of P1.56mm Indoor black LED Display

Pixel pitch	1.56mm	Size of pixel	1.0mm (circle)
Size of module	150mm×169mm	Pixel of module	96 ×108
Size of cabinet	600mm×338mm	Resolution of cabinet	384 ×216
Area of cabinet	0.2028 m ²	Density of pixel	409,500dots/m ²
Pixel configuration	1R1PG1B	Red wavelength	625±2nm
Green wavelength	525±2nm	Blue wavelength	470±2nm
Gray Scale	16bits	Best viewing distance	≥5feet
Horizon/vertical viewing angle	160°/160°	Maximum power consumption	<800 W / m ²
Brightness	900cd/ m ²	IP grade	IP20
Control method	Synchronization	Color temperature	6500K
Frame frequency	60Hz	Driving method	Constant 1/27scanning
Working voltage	AC220V/110V±10%	Refresh frequency	≥30Hz
MTBF	More than 10,000 hours	Working temperature	-20°C-- +45°C
		Panel weight	18lb
		Life span	100,000 hours



GLIC LED Displays Inc/510 Coralridge Pl, Suite 101, City of Industry, Ca 91746

Phone: 626-236-0920 Fax: 626-316-7232 Email: glic2000@hotmail.com Website: www.generallinkintl.com